



DESCRIPTION

A premium quality full matte acrylic coating, especially formulated for ceilings. Provides a beautiful uniform mat finish, has a long open time and provides maximum diffused light. Excellent hiding, easy to apply, spatter resistant. Provides a mildew resistant coating formulated without ammonia, it is low odor, user friendly and environmentally sensitive.

PERFORMANCE GUIDE

| | |
|----------------------------|--|
| Weather Resistance | No recommended for exterior use. |
| Heat Resistance | 60° C |
| Water Resistance | Washable. Allow 7 days after application for firm to cure. |
| Abrasion Resistance | Resists marring, less so in darker colors. |
| Solvent Resistance | Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols. |



VOC (Volatile Organic Compounds): EU limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60o), 30 g/l (2010). This product contains max 29 g/l VOC

PERFORMANCE FEATURES

- Paint + Primer in one.
- Contains mildewcide to control fungi.
- All Acrylic premium quality.
- Tones down ceiling glare and provides maximum diffused light.
- Dries to a beautiful, decorative flat finish.
- Cleans easily, Spatter-resistant.
- Easy application and clean up, quick recoat.
- Excellent opacity.
- Odorless without ammonia and other solvents.
- Ammonia free



Colors:

White and may be tinted to light colors from PPG VOICE OF COLOUR™ fandeck




Toxicity:

Formulated without lead or mercury.



Gloss Level: 0-2 at 60 degree viewing angle.



Spreading Rate

10 – 11 m²/L

Actual coverage may vary depending on substrate and application method

Volume Solids

37%+/- 1%

Wet Film Thickness

97 micrometres

Dry Film Thickness

36 micrometres

Dry Time at 20°C

1 hour to touch, 2-4 hours to recoat

Resin:

Acrylic Resin

Thinning

5% water if necessary

For Application By

Brush, Roller, Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surface to be painted must be clean and free of dirt, grease, flaking paint and mildew. Dull glossy areas by sanding. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flatting should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. Apply two coats of 17-10 CEILING PAINT, Ultra Flat Ceiling Paint after priming the surface as outlined below.

New Plaster, Gypsum Board: Prime with a full coat of DRP 514 Eco Micronized Stabilizing Waterborne Primer or DRP 512 Waterproofing Sealer Solventborne Primer.

Masonry, Concrete, Bricks: Prime with DRP 514 Eco Micronized Stabilizing Waterborne Primer or DRP 508 Alkali Resistant Waterborne Acrylic Primer.

Previously Painted Surfaces: If surface is sound, prime with DRP 516 Eco All Purpose Waterborne Acrylic Primer. Fill nail holes and cracks and sand when dry. Spot prime patched surfaces with DRP 516 Eco All Purpose Waterborne Acrylic Primer. If previous is old porous lime, apply and overall coat of DRP 512 Waterproofing Sealer Solventborne Primer.

New Wood: Prime surfaces with DRP 510 Multi Purpose Solventborne Primer or DRP 516 Eco All Purpose Waterborne Acrylic Primer.

APPLICATION

Stir thoroughly before and during use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water, only if necessary. Do not apply at temperatures below 10oC. Drying times are longer in cool/moist conditions.

CLEAN UP

Clean equipment in warm, soapy water after painting. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-octyl-2H-isothiazol-3-one and butylcarbamate-3-iodo-2-propynyl. May produce an allergic reaction. • Do not get in eyes, on skin, or on clothing • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. • Keep container tightly closed • Avoid release to the environment • Contains a biocidal product with fungicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6) and 2-octyl-2H-isothiazol-3-one (26530-20-1) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

POISON CENTER TEL.: +302107793777

Packaging and Storage

Sizes: 1 litre, 3 litres, 10 litres

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5

