


31-68 PARAMOUNT™ PU Waterborne Concrete & Stone Stain & Sealer

For Interior / Exterior use



DESCRIPTION

A water based odorless - non yellowing- acrylic polyurethane concrete stain. It allows the beauty of natural stones to show through while allowing long lasting protection. It features deep penetration, not film forming, will not peel, easy application, quick drying. Ideal for porous stones, mosaic, and artificial buildings materials such as brick roof tiles and concrete. Suitable for light use on pre-cast concrete basement, factory and warehouse floors.

PERFORMANCE GUIDE

Weather Resistance	Excellent resistance to weather.
Heat Resistance	Not applicable.
Water Resistance	Excellent rain and condensation resistance.
Abrasion Resistance	Good resistance to abrasion.
Solvent Resistance	Good resistance to alcohols and common house hold chemicals. Sensitive to aromatic hydrocarbons and other strong solvents



VOC (Volatile Organic Compounds): EU Limit value for this product category A/i WB (One pack performance coating), 140g/l (2010). This product contains max 139g/L VOC.

PERFORMANCE FEATURES

- Waterborne Advanced Technology
- Polyurethane Tough Protection
- Deep Penetration, Waterproofs and Enhances Color
- Excellent Gloss Retention and Weather Resistance
- Protects and Beautifies Concrete and Other Porous Masonry
- Quick Dry, Same Day Recoat




Colors:
Clear. Do not tint



Toxicity:
Formulated without lead or mercury.



Gloss Level: 20-25 at 60 degrees viewing angle



Spreading Rate

8-10 m²/L depending on surface porosity
Actual coverage may vary depending on substrate and application method

Volume Solids

31.70% +/- 1%

Wet Film Thickness

Minimum

Dry Film Thickness

Minimum

Dry Time at 20°C

30 minutes to touch
2-3 hours to recoat

Resin:

PU Acrylic Resin

Thinning

Thin first coat 1/1 with water.

For Application By

Brush, Spray or Roller

DIRECTION FOR USE

SURFACE PREPARATION

The surface must be dry and clean with all traces of grease oil, wax, sealers and salts. Smooth towelled surfaces or non-porous concrete, must be etched before applying 41-98 PARAMOUNT PU Waterborne Concrete & Stone Stain & Sealer. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flattening should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment.

APPLICATION

Stir thoroughly before and during use. Apply by brush, roller or spray. First coat must be thinned 1/1 with water and after drying 1 or 2 coats without thinning. Allow 3 hours between coats. Do not apply when temperature is below 10°C or against the hot sun. Drying times are longer in cool/moist conditions.

Notice

Uneven gloss might show on film if applied when high humidity is present, which disappears in time.

CLEAN UP

Clean equipment in warm, soapy water.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes: 0,75 litres, 2,25 litres

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5

