



31-69 PARAMOUNT™ Waterborne Concrete Facades & Stain Sealer Based On Silanes & Fluorides For Interior / Exterior use



DESCRIPTION

Ready to use water and oil repellent colorless solution based on fluorides, silanes and siloxanes compounds. Penetrates inside pores, does not form a surface film or change the natural appearance of the materials, allowing the surface to breath. Effective water repellent protection on vertical and horizontal alkaline surfaces including porous floors. Prevents efflorescence, frost damage and formation of mildew and moss. Suitable for porous materials such as natural stones, concrete, bricks, porous marbles, porous ceramic tiles, concrete baths and showers. Do not use on non – porous materials.

PERFORMANCE GUIDE

Weather Resistance	Excellent resistance to weather.
Water Resistance	Excellent rain and condensation resistance.



VOC (Volatile Organic Compounds): EU Limit value for this product category A/c WB (exterior walls of mineral substrate), 40g/l (2010). This product contains zero (0) VOC.

PERFORMANCE FEATURES

- Waterborne Advanced Technology
- Water and Oil Repellent Effect on Vertical and Horizontal Alkaline Surfaces
- Natural Appearance Look, Breathable Film
- Waterproofs, Protects and Seals Surface
- Prevents Efflorescence, Frost Damage and Formation of Mildew and Moss



Colors:

Milky, dries clear. Do not tint



Toxicity:

Formulated without lead or mercury.



Gloss Level: Matt

Spreading Rate

5-7 m²/L depending on surface porosity

Actual coverage may vary depending on substrate and application method

Volume Solids

4.50%+/- 1%

Wet Film Thickness

Minimum

Dry Film Thickness

Minimum

Dry Time at 20°C

1 hour to touch

Resin:

Silanes and siloxanes

Thinning

Do not thin. Ready to use

For Application By

Brush, Spray or Roller

DIRECTION FOR USE

SURFACE PREPARATION & APPLICATION

Surface must be clean, dry (or slightly damp), free of dust, dirt, grease, salts and mildew. Cover and protect adjoining areas. Cover plants. Do not apply directly on sunlight. Stir product prior of using. Apply generously with soft brush or roller, for larger areas apply by spray, until the substrate is saturated and a fluid film runs down the building surface. On horizontal surfaces the application can be done by a squeegee. Excessive material must be removed.

Note: If a second coat is required it must be applied while first coat is still wet (wet on wet application). Recoat is allowed after 6 months.

CLEAN UP

Clean equipment in warm, soapy water.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes: 1 litre, 5 litres, 10 litres

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5