



PARAMOUNT PU WATERBORNE FLOOR & TRIM VARNISH & SEALANT 41-22 GLOSS /41-23 SATIN

For Interior use



DESCRIPTION

A premium quality waterbased varnish that combines the attributes of polyurethane and acrylic to produce a clear, durable finish. Dries quickly with no odor. Use on new or previously painted, stained, or varnished interior wood surfaces, including floors. Provides resistance to abrasion and protection against alcohol, water, stains and most household chemicals. Can also be used as a protective coating over sound previously painted surfaces. Formulated without lead.

PERFORMANCE GUIDE

Weather Resistance	Not recommended for exterior use
Water Resistance	Resist's water and alcohol
Abrasion Resistance	Good resistance to abrasion
Solvent Resistance	Good resistance to alcohols and common household chemicals. Sensitive to aromatic hydrocarbons and other strong solvents.



VOC (Volatile Organic Compounds): EU Limit value for this product category A/i WB (One pack performance coating), 140g/l (2010). This product contains max 139g/L VOC.

PERFORMANCE FEATURES

- Waterborne Advanced Technology
- Scuff & Scratch Resistant
- Non Yellowing, Quick Dry & Recoat
- Long Lasting Protection



Colors:
Clear



Toxicity:
Formulated without lead or mercury.



Gloss Level: 41-22 Gloss and 41-23 Satin

Spreading Rate

9 – 10 m²/L

Actual coverage may vary depending on substrate and application method

Volume Solids

30%+/- 1%

Wet Film Thickness

111 micrometres

Dry Film Thickness

33 micrometres

Dry Time at 20°C

1 hour to touch – 3-4 hours to recoat

Resin:

Acrylic Resin

Thinning

5% water

For Application By

Brush, Roller, Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surfaces to be finished must be free of wax, dirt, grease, dust and other contaminants. Dull glossy areas by sanding (do not use steel wool). Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flatting should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment.

New wood: Sand smooth using fine sandpaper following the grain of the wood.

Old finishes: Remove old finishes in poor condition. Sand old finishes in good condition until smooth.

APPLICATION

Stir thoroughly before use but do not shake. Apply as received in the container. Thin, if necessary, with up to 5% of clean water. Apply by brush, roller, airless spray or applicator pad. Apply along the wood grain in thin, even coats. Maintain a wet edge during application - avoid working back into partially dried areas. PARAMOUNT PU Waterborne Floor & Trim Varnish & Sealant first appears milky but dries to a clear finish. Apply two or more coats over previous finishes and at least three coats on new wood. Sand lightly between coats to ensure a smooth finish but do not use steel wool. Do not apply at air and surface temperatures below 10o C or under humid conditions.

CLEAN UP

Clean equipment in warm, soapy water after painting.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

POISON CENTER TEL.: +302107793777

Packaging and Storage

Sizes: 0,75 litres, 2,25 litres

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5