



DESCRIPTION

A superb quality satin alkyd enamel that lasts for years indoors. Recommended for use on primed wood and metal surfaces. Features excellent levelling, quick dry, durability, color retention and easy washability. The low odor characteristics result in more pleasant interior application. Formulated without lead.

PERFORMANCE GUIDE

Heat Resistance	Up to 120°C. Continuous heat will cause premature yellowing and embitterment
Water Resistance	Good resistance to water and condensation. Scrubbable
Abrasion Resistance	Excellent resistance to abrasion.
Solvent Resistance	Good resistance to aliphatic solvents and alcohols. Sensitive to aromatic hydro carbons and other strong solvents.



VOC (Volatile Organic Compounds): EU Limit value for this product category A/d SB: Interior/Exterior trim and cladding paints for wood and metal. Ready to use product contains maximum 299g/L which is under the relevant EU limit values: 300g/l (2010).

PERFORMANCE FEATURES

- Has superb levelling and hiding qualities.
- Excellent sag resistance.
- Hard wearing, durable, weather resistant.
- Low odour during application.
- Elegant satin finish.
- Suitable for high use or commercial areas.



Colors:

White and over 2,200 tinted colors are available from PPG VOICE OF COLOUR™ fandeck.




Toxicity:

Formulated without lead or mercury.



Gloss Level: 25-30 at 60 degree viewing angle



Spreading Rate

15 – 16 m²/L

Actual coverage may vary depending on substrate and application method

Volume Solids

42%+/- 1%

Wet Film Thickness

72 micrometres

Dry Film Thickness

30 micrometres

Dry Time at 20°C

3 hours to touch - 16 hours to recoat

Resin:

Acrylic Resin

Thinning

5% low odour white spirits

For Application By

Brush, Roller, Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surface to be painted must be free of all loose material such as dust, flaking and peeling paint. The surface must be clean with all traces of grease, oil, and dirt removed. Remove loose material by scraping and sanding. Sand glossy surfaces to a dull finish. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flattening should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. Apply two coats of 41-16 ULTRA Alkyd Based Satin Wood & Metal Enamel, after priming as outlined below.

New Wood: Spot prime all caulked nail holes and patches with DRP 510 Multi Purpose Solventborne Primer. Allow to dry, then apply a full coat of Alkyd Undercoat. Sand to a smooth surface.

Ferrous Metal: Remove rust and loose material before priming exposed metal with DRP 506 Rust Protect Solventborne Primer.

Previously Painted Surfaces: Prime with DRP 510 Multi Purpose Solventborne Primer.

APPLICATION

Stir thoroughly before and during use. Apply by brush, roller or spray. Thin 5% with low odour white spirits. Do not apply when air or surface temperature is below 10oC or when the humidity is high. Drying times are longer under cool/moist conditions.

CLEAN UP

Clean brushes and equipment with white spirits.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

WARNING. Contains: Naphtha (petroleum), heavy hydrogenated. • Flammable liquid and vapour. • May cause drowsiness or dizziness. • Harmful to aquatic life with long lasting effects. • Repeated exposure may cause skin dryness or cracking. • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. • Contains: cobalt bis (2-ethylhexanoate), benzofuran-1,3-dione and 2-Butanone oxime. May produce an allergic reaction. • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. • In case of fire: Use carbon dioxide, foam, chemical powder to extinguish. • Wear protective gloves, protective clothing, eye protection, face protection. • Use only outdoors or in a well-ventilated area. • Call a POISON CENTER or a doctor if you feel unwell. • Keep out of reach of children. • Avoid release to the environment. • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. • Store locked up. • Keep cool. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777



Packaging and Storage

Sizes: 0,75 litres, 2,25 litres

Flash Point: 44oC (Abel)

Storage: PAINTS, flammable liquid

For Advising – Technical Services call: 2106620713-5