



## 41-29 PARAMOUNT™ NON-DRIP GEL WOOD VARNISH & DECK STAIN

For Interior / Exterior use



### DESCRIPTION

A high quality water based impregnating wood varnish. Innovative gel non drip formula provides ease of application on vertical or horizontal wood surfaces. Features deep penetration, weather resistance, waterproof breathable film while it doesn't flake or peel. It offers protect against UV sun rays, using new technology UV filters. It contains mildewcide and algacide for prevention of mildew. Ideal for new or old bare wood doors, windows, lawn, furniture, railings, pergolas etc. It's odorless, transparent film enhances the beauty of wood texture. Easy application, dries quickly. Available in various colors using PPG's PARAMOUNT SERIES Color Card.

### PERFORMANCE GUIDE

<b>Weather Resistance</b>	Excellent resistance to weather.
<b>Heat Resistance</b>	Not applicable.
<b>Water Resistance</b>	Excellent rain and condensation resistance.
<b>Abrasion Resistance</b>	Good resistance to abrasion.
<b>Solvent Resistance</b>	Good resistance to alcohols and common house hold chemicals. Sensitive to aromatic hydrocarbons and other strong solvents



**VOC (Volatile Organic Compounds):** EU Limit value for this product category A/f WB (Interior and Exterior minimal build woodstains), 130g/l (2010). This product contains max 60g/L VOC

### PERFORMANCE FEATURES

- Waterborne Advanced Technology
- Protects Against UV, New Innovative Filters
- Contains Mildew & Algicide Protection
- Deep Penetration, Prevents Cracking & Peeling
- Waterproof Breathable Film



#### Colors:

Can be tinted to produce colors using PPG's PARAMOUNT SERIES Color Card



#### Toxicity:

Formulated without lead or mercury.

#### Spreading Rate

12 - 15 m<sup>2</sup>/L depending on wood porosity  
*Actual coverage may vary depending on substrate and application method*

#### Volume Solids

40%+/- 1%

#### Wet Film Thickness

111 micrometres

#### Dry Film Thickness

33 micrometres

#### Dry Time at 20°C

30 minutes to touch  
3-4 hours to recoat

#### Resin:

Acrylic Resin

#### Thinning

Do not thin

#### For Application By

Brush, Roller, Spray

## DIRECTION FOR USE

### SURFACE PREPARATION

Surface must be clean, dry and free of dirt, oil or grease. Completely remove old or poorly adhering varnish to expose new wood. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flattening should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. On tropical wood wash down with nitro thinner to remove resins that may lengthen dry times. If mildew is evident it must be removed by scrubbing with a commercial mildew wash, following manufacturer's direction and cautions.

**NOTE:** For further protection if necessary, against fungi and wood rotting microorganisms use one coat 41-90 PARAMOUNT Waterborne Wood Preservative. Afterwards apply one or two coats 41-89 PARAMOUNT Non Drip Gel Wood Varnish & Deck Stain.

### APPLICATION

Stir thoroughly before and during use. Apply one or two coats without thinning by brush, roller or spray. The actual color of the varnish can vary depending on number of coats, natural color of wood, texture and grain porosity. Do not apply when temperature is below 10° C or against the hot sun. Drying times are longer in cool/moist conditions.

### CLEAN UP

Clean equipment in warm, soapy water.

### PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Contains: 1,2-benzisothiazol-3(2H)-one (2634-33-5), reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9) & butylcarbamate-3-iodo-2-propynyl (55406-53-6). May produce an allergic reaction. • Do not get in eyes, on skin, or on clothing • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. • Keep container tightly closed. • Avoid release to the environment • Containing a biocidal product with fungicidal properties. • Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6) to protect the coating (film). • Do not empty into drains. • The residual water from cleaning of the working equipment must not get into the ground or into surface waters. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

### Packaging and Storage

**Sizes:** 0,75 litres, 2,25 litres

**Flash Point:** none

**Storage:** not hazardous, no special requirements

**For Advising – Technical Services call: 2106620713-5**

