



41-31 PARAMOUNT™ WATERBORNE PENETRATING WOOD STAIN

For Interior / Exterior use



DESCRIPTION

A water based odorless penetrating stain formulated with special resins. Its depth and clarity of tone emphasize the natural pattern and characteristics of the wood grain it features uniform penetration and quick drying. Can be tinted to produce colors using PPG' s PARAMOUNT SERIES Color Card.

PERFORMANCE GUIDE

| | |
|----------------------------|-----------------|
| Weather Resistance | Not applicable. |
| Heat Resistance | Not applicable. |
| Water Resistance | Not applicable. |
| Abrasion Resistance | Not applicable. |
| Solvent Resistance | Not applicable. |



VOC (Volatile Organic Compounds): EU Limit value for this product A/f WB (Interior and Exterior minimal build woodstains), 130g/l (2010). This product contains max 60g/L VOC.

PERFORMANCE FEATURES

- Waterborne Advanced Technology
- Impregnating High Transparent Pigments
- Non Yellowing – Fade Resistant
- Breathable Film



Colors:

Can be tinted to produce colors using PPG' s PARAMOUNT SERIES Color Card




Toxicity:

Formulated without lead or mercury.



Gloss Level: 0-5 at 60 degree viewing angle.



Spreading Rate

8-10 m²/L depending on wood porosity
Actual coverage may vary depending on substrate and application method

Volume Solids

12.35%+/- 1%

Wet Film Thickness

Minimum

Dry Film Thickness

Minimum

Dry Time at 20°C

30 minutes to touch
1-2 hours to recoat

Resin:

Acrylic Resin

Thinning

Do not thin

For Application By

Brush, Sponge or Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surface must be clean, dry and free of dirt, oil or grease. Completely remove old or poorly adhering varnish and paint to expose new wood. Surfaces must be sanded and remove dust. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flatting should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. On tropical wood wash down with nitro thinner to remove resins that may lengthen dry times. If mildew is evident it must be removed by scrubbing with a commercial mildew wash, following manufacturers direction and cautions.

APPLICATION

Surface must be clean, dry and free of dirt, oil or grease. Completely remove old or poorly adhering varnish and paint to expose new wood. Surfaces must be sanded and remove dust. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flatting should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. On tropical wood wash down with nitro thinner to remove resins that may lengthen dry times. If mildew is evident it must be removed by scrubbing with a commercial mildew wash, following manufacturers direction and cautions.

NOTICE: If greater protection against woodworm, insects, fungi, and other micro-organisms is needed use 41-90 PARAMOUNT Waterborne Wood Preservative.

CLEAN UP

Clean equipment in warm, soapy water.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes: 0,75 litres, 2,25 litres

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5

