



DRN 17 CHALKBOARD PAINT

Waterborne chalkboard paint
For Interior use



DESCRIPTION

A premium acrylic based charcoal paint, turns virtually any interior surface into a chalkboard. Available in any deep color. Dries quickly to a decorative finish that is extremely durable. Is formulated to minimize odor and is ammonia free. Soap and water cleanup.

PERFORMANCE GUIDE

Water Resistance	Washable. Allow 7 days after application for firm to cure.
Abrasion Resistance	Resists marring, less so in darker colors.
Solvent Resistance	Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



VOC (Volatile Organic Compounds): EU limit value for this product category A/I type WB: Decorative effect coating, 200 g/l (2010). This product contains max 39 g/l VOC.

PERFORMANCE FEATURES

- Waterborne Advanced Technology
- Turns Walls to Fun and Creative Surfaces
- Dries to a Decorative Finish That is Extremely Durable
- Resists Spattering During Application
- Soap and Water Clean UP
- Quick Dry, Same Day Recoat



Colors:

Black, available also in all medium and deep colors




Toxicity:

Formulated without lead or mercury.



Gloss Level: Low Sheen



Spreading Rate

11 – 12 m²/L

Actual coverage may vary depending on substrate and application method

Volume Solids

35%+/- 1%

Wet Film Thickness

67 micrometres

Dry Film Thickness

23 micrometres

Dry Time at 20°C

1 hour to touch, 2-4 hours to recoat

Resin:

Acrylic Resin

Thinning

Not applicable

For Application By

Brush, Roller, Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surface to be painted must be clean and free of dirt, dust, grease and flaking paint. Remove loose material by scraping and sanding. Dull glossy areas by sanding. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flattening should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. Apply two coats of DRN 17 Waterborne Chalkboard Paint, after priming as outlined below.

New Wood: Spot prime all caulked nailholes and patches with DRP 516 Eco All Purpose Waterborne Acrylic Primer. Allow to dry, then apply a full coat of Primer. Sand to a smooth surface.

New Plaster, Gypsum Board: Prime with a full coat of DRP 514 Eco Micronized Stabilizing Waterborne Primer.

Ferrous Metal: Remove rust and loose material before priming exposed metal with DRP 506 Rust Protect Solventborne Primer.

Previously Painted Surfaces: Prime with DRP 516 Eco All Purpose Waterborne Acrylic Primer.

APPLICATION

Stir thoroughly before use. Apply one or two coats. For best results, use nylon/polyester brush, roller or spray. Thin 5% with clean water. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 10°C.

CAUTION: Because of the additives used in some varieties of colored chalk, which can leave colored "marking" when erased, we recommend using lighter colored chalk designed for use on chalkboard.

CLEAN UP

Clean brushes and equipment in warm, soapy water immediately after use.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes: 1 litre

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5

