

## DRN 38 Wonder-Tones™ Bath & Spa Satin Mildew Resistant Paint

For Interior use



### DESCRIPTION

A premium quality 100% acrylic satin enamel, specially formulated for optical performance in high humidity environments such as bath, spa, kitchens and other areas. Designed to have excellent adhesion over clean hard surfaces and provides a mildew resistant coating. It is ammonia free, has no unpleasant odor and features a spatter-resistant formulation, fast dry, and excellent covering qualities.

### PERFORMANCE GUIDE

<b>Weather Resistance</b>	No recommended for exterior use.
<b>Heat Resistance</b>	Up to 65o C
<b>Water Resistance</b>	Excellent Water Resistance. Not for immersion service.
<b>Abrasion Resistance</b>	Good resistance to abrasion.
<b>Solvent Resistance</b>	Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



**VOC (Volatile Organic Compounds):** EU Limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30g/l (2010). This product contains max 29g/l VOC

### PERFORMANCE FEATURES

- Paint + Primer in one.
- For bathrooms, spa, kitchens, laundries and inside areas subject to humidity, water splash and frequent cleaning.
- Contains a mildewcide to control fungal growth.
- Spatter resistance application.
- Good adhesion to new and previously painted surfaces.
- Ammonia free



#### Colors:

White and over 2,200 tinted colors are available from PPG VOICE OF COLOUR™ fandeck




#### Toxicity:

Formulated without lead or mercury.



**Gloss Level:** 20-25 at 60 degree viewing angle.



#### Spreading Rate

14 -15 m<sup>2</sup>/L

*Actual coverage may vary depending on substrate and application method*

#### Volume Solids

34%+/- 1%

#### Wet Film Thickness

72 micrometres

#### Dry Film Thickness

24 micrometres

#### Dry Time at 20°C

2 hours to touch, 8 hours to recoat

#### Resin:

Acrylic Resin

#### Thinning

5% water

#### For Application By

Brush, Roller, Spray

## DIRECTION FOR USE

### SURFACE PREPARATION

Surface to be painted must be clean and free of dirt, dust, grease, wax, loose material or flaking paint, and mildew. Clean hard or previously painted surfaces thoroughly with detergent and water. Rinse well. Dull glossy areas by sanding. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flatting should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment.

Note: If mildew is present, remove with a commercial mildew wash, following manufacturer's directions and cautions. Apply two coats of DRN 38 Wonder-Tones Bath & Spa Satin Mildew Resistant Paint.

**New Walls, Gypsum Board and Plaster:** Prime with DRP 514 Eco Micronized Stabilizing Waterborne Primer.

**Previously Painted Surfaces:** Ensure surfaces are thoroughly clean and sound. Prime with 1 coat DRP 520 Bath & Spa Mildew Resistant Waterborne Primer.

**Wood:** Prime with DRP 516 Eco All Purpose Waterborne Acrylic Primer.

### APPLICATION

Stir paint thoroughly before use. Apply by brush, roller or spray. Thin 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

### CLEAN UP

Clean equipment in warm, soapy water promptly after painting.

### PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. • Do not get in eyes, on skin, or on clothing • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. • Avoid release to the environment • Contains a biocidal product with fungicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6) and 2-octyl-2H-isothiazol-3-one (26530-20-1) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

POISON CENTER TEL.: +302107793777

### Packaging and Storage

**Sizes:** 1 litre, 3 litres

**Flash Point:** none

**Storage:** not hazardous, no special requirements

**For Advising – Technical Services call: 2106620713-5**

