

**DRP 520 BATH & SPA MILDEW
RESISTANT WB PRIMER**
Waterborne Anti- Mould Coating
For Interior use



DESCRIPTION

A high quality, 100% acrylic primer formulated to be used where mould and midew growth is likely. It provides outstanding adhesion and sealing, and can be applied under acrylic or enamel paints as well as over new and previously painted surfaces. Recommended for use in bathrooms, spa, kitchens and other areas that may be subject to high humidity. DRP520 Bath & Spa Mildew Resistant Waterborne Primer spatter-resistant formula is odorless and easy to apply.

PERFORMANCE GUIDE

Weather Resistance	No recommended for exterior use.
Heat Resistance	Up to 60°C.
Water Resistance	Excellent Water Resistance.
Solvent Resistance	Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



VOC (Volatile Organic Compounds): EU limit value for this product category A/g type WB: Primers, 30 g/l (2010). This product contains max 29 g/l VOC.

PERFORMANCE FEATURES

- For bathrooms, spa, kitchens, laundries and inside areas subject to humidity and frequent cleaning.
- Contains a mildewcide to control fungal growth.
- Quick dry allows recoat same day.
- Spatter resistant application.
- Good adhesive to new and previously painted surfaces.
- Gives a smooth surface for high quality finish.



Colors:

White. May be tinted to light colors for additional hiding




Toxicity:

Formulated without lead or mercury.



Gloss Level: Flat



Spreading Rate

9-10 m²/L

Actual coverage may vary depending on substrate and application method

Volume Solids

34%+/- 1%

Wet Film Thickness

111 micrometres

Dry Film Thickness

38 micrometres

Dry Time at 20°C

1 hour to touch

2 hours to recoat

Resin:

Acrylic Resin

Thinning

5% water

For Application By

Brush, Roller, Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surface to be painted must be clean and free of dirt, dust, grease, wax, loose material or flaking paint, and mildew. Clean hard or previously painted surfaces thoroughly with detergent and water. Rinse well. Dull glossy areas by sanding. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flattening should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment.

Note: If mildew is present, remove with a commercial mildew wash, following manufacturer's directions and cautions. Apply 1 coat of DRP 520 Bath & Spa Mildew Resistant Waterborne Primer.

APPLICATION

Stir thoroughly before and during use. Apply by brush, roller or spray. Thin as 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

CLEAN UP

Clean equipment in warm, soapy water promptly after painting.

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. • Do not get in eyes, on skin, or on clothing • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. • Avoid release to the environment • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

Contains a biocidal product with fungicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes: 0,75litre, 2,5 litres

Flash Point: None

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5

