

DRN 533 Wonder-Hide™
Interior Ultra Flat Emulsion
For Interior use



DESCRIPTION

Emulsion paint for interior use with excellent hiding qualities. Provides a uniform Ultra Matte Finish, doesn't show wall imperfections. Used on properly prepared plaster, concrete, bricks, gypsum board. It features durable film, fast drying, ease of application. Spatter resistance formula. Ammonia free.

PERFORMANCE GUIDE

Weather Resistance	No recommended for exterior use.
Heat Resistance	60o C
Water Resistance	Washable. Allow 7 days after application for firm to cure.
Abrasion Resistance	Good resistance to abrasion.
Solvent Resistance	Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



VOC (Volatile Organic Compounds): EU limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30 g/l (2010). This product contains max 29 g/l VOC.

PERFORMANCE FEATURES

- Paint + Primer in one.
- Hides most imperfections
- Dries to a beautiful, decorative flat finish.
- Spatter-resistant, low odour.
- Easy application and clean up, quick recoat.
- Excellent opacity
- Ammonia free



Colors:

White and over 2,200 tinted colors are available from PPG VOICE OF COLOUR™ fandeck




Toxicity:

Formulated without lead or mercury.



Gloss Level: 0-2 at 60 degree viewing angle



Spreading Rate

10-11 m²/L

Actual coverage may vary depending on substrate and application method

Volume Solids

40%+/- 1%

Wet Film Thickness

100 micrometres

Dry Film Thickness

40 micrometres

Dry Time at 20°C

1 hour to touch, 2-4 hours to recoat

Resin:

Vinyl Acrylic Resin

Thinning

5% water

For Application By

Brush, Roller, Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surface to be painted must be clean, dry and free of grease, dirt, dust, flaking paint and mildew. Dull glossy areas by sanding. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flattening should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. Apply two coats of DRN 533 WONDER-HIDE Interior Ultra Flat Emulsion after priming the surface as outlined below.

New Plaster, Gypsum Board: Prime with a full coat of DRP 514 Eco Micronized Stabilizing Waterborne Primer or DRP 510 Multi Purpose Solventborne Primer.

Masonry, Concrete, Bricks: DRP 508 Alkali Resistant Waterborne Acrylic Primer or DRP 512 Waterproofing Sealer Solventborne Primer.

Previously Painted Surfaces: If surface is sound, prime with DRP 508 Alkali Resistant Waterborne Acrylic Primer. Fill nail holes and cracks and sand when dry. Patched surfaces should be spot-primed with DRP 508 Alkali Resistant Waterborne Acrylic Primer. If previous coating is old porous lime, apply an overall coat of DRP 512 Waterproofing Sealer Solventborne Primer.

New Wood: Prime surfaces with DRP 516 Eco All Purpose Waterborne Acrylic Primer or DRP 510 Multi Purpose Solventborne Primer

APPLICATION

Stir paint thoroughly before use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

CLEAN UP

Clean equipment in warm, soapy water after painting. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. • Do not get in eyes, on skin, or on clothing • Avoid release to the environment Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes: 1 litre, 3 litres, 10 litres

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5

