



R 5149 REGENCY™ Stain & Scuff Resistant Ceramic Matte Paint

For Interior use



DESCRIPTION

All Acrylic premium quality stain and scuff resistant coating. Highly durable to household stains preventing them from soaking into the film. It creates a protective surface with the highest resistance to stains such as, tea, juice, coffee, soft drinks, ketchup, mustard, mud, chocolate and non-permanent markers. Innovative scuff-resistant formula, it will hold up to repeated cleaning without causing damage to the paint, keeping walls looking freshly painted. Easy to clean, ideal for use on children rooms schools, nurseries, hotels, locker rooms, hospitals and other commercial spaces. Produces a beautiful matte finish with excellent hiding, fast dry and it is spatter free. Odorless, formulated without ammonia, provides a mildew resistant coating.

CLEANING: Full properties are achieved after two weeks completing the painting. Stains and scuff marks can be removed with a wet sponge, water and mild clear soap.

PERFORMANCE GUIDE

Weather Resistance	No recommended for exterior use.
Heat Resistance	60o C.
Water Resistance	Washable. Allow two weeks after application for firm to cure.
Abrasion Resistance	Excellent abrasion resistance
Solvent Resistance	Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



VOC (Volatile Organic Compounds): EU Limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30g/l (2010). This product contains max 5g/l VOC

PERFORMANCE FEATURES

- Paint + Primer in one.
- Easy to clean, resist staining based on its microscopic ceramic beads technology
- Innovative scuff-resistant formula, it will hold up to repeated cleaning without causing damage to the paint, keeping walls looking freshly painted.
- Dries to an attractive matte finish.
- Spatter-resistant, excellent opacity.
- Contains mildew side to control fungi.
- It is odorless, without ammonia
- Dries quickly
- Ammonia free



Colors:

White and over 2,200 tinted colors are available from PPG VOICE OF COLOUR™ fandeck.




Toxicity:

Formulated without lead or mercury.



Gloss Level: 0-5 at 60 degree viewing angle.



Spreading Rate

12 -14 m²/L

Actual coverage may vary depending on substrate and application method

Volume Solids

33%+/- 1%

Wet Film Thickness

97 micrometres

Dry Film Thickness

33 micrometres

Dry Time at 20°C

1 hour to touch | 2-4 hours to recoat

Resin:

Acrylic Resin

Thinning

5% water if necessary

For Application By

Brush, Roller, Spray

DIRECTION FOR USE

SURFACE PREPARATION

Surface to be painted must be clean and free of dirt, grease, flaking paint and mildew. Dull glossy areas by sanding. Dry sanding, flame cutting and /or welding of the dry paint film will give rise to dust fumes. Wet sanding/flatting should be used wherever possible. • Ensure good ventilation during application and drying. Use suitable respiratory protective equipment. Apply two coats of R 5149 REGENCY, Stain & Scuff Resistant Ceramic Matte Paint after priming the surface as outlined below.

New Plaster, Gypsum Board: Prime with a full coat of DRP 514 Eco Micronized Stabilizing Waterborne Primer or DRP 510 Multi Purpose Solventborne Primer.

Masonry, Concrete, Bricks: DRP 512 Waterproofing Sealer Solventborne Primer or DRP 508 Alkali Resistant Waterborne Acrylic Primer.

Previously Painted Surfaces: If surface is sound, prime with DRP 508 Alkali Resistant Waterborne Acrylic Primer. Fill nail holes and cracks and sand when dry. Spot prime patched surfaces with DRP 516 Eco All Purpose Waterborne Acrylic Primer. If previous is old porous lime, apply and overall coat of DRP 512 Waterproofing Sealer Solventborne Primer.

New Wood: Prime surfaces with DRP 510 Multi Purpose Solventborne Primer or DRP 516 Eco All Purpose Waterborne Acrylic Primer.

APPLICATION

Stir thoroughly before and during use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water, only if necessary. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

CLEAN UP

Clean equipment in warm, soapy water after painting. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation

PRECAUTIONS HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

• If medical advice is needed, have product container or label at hand • Keep out of reach of children • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-octyl-2H-isothiazol-3-one and butylcarbamate-3-iodo-2-propynyl. May produce an allergic reaction. • Do not get in eyes, on skin, or on clothing • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. • Keep container tightly closed • Avoid release to the environment • Contains a biocidal product with fungicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6) and 2-octyl-2H-isothiazol-3-one (26530-20-1) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

POISON CENTER TEL.: +302107793777

Packaging and Storage

Sizes: 1litre, 3litres, 10 litres

Flash Point: none

Storage: not hazardous, no special requirements

For Advising – Technical Services call: 2106620713-5

